



SPECIFICATIONS

ELECTRICAL

- Contact Current Rating : 1 Ampere
- Contact Resistance : 20 mΩ Max
- Insulator Resistance : 1,000 MΩ Min
- Dielectric Withstanding Voltage : 1,000V AC RMS 60 Seconds

MECHANICAL

- Insertion Force : 340 g Max / Pin
- Extraction Force : 50 g Min / Pin

MATERIAL

- Insulator : PBT, UL 94V-0
- Contact : Phosphor Bronze
- Contact Plated : Tin Plated

Operation Temperature : - 25°C to + 85°C

| ICSAXTBIBC | DIMENSION | | | |
|------------|-------------------------------------|-------------------------------------|-------------------------------------|-------------------------------------|
| | A ^{+0.10} _{-0.10} | B ^{+0.12} _{-0.12} | C ^{+0.15} _{-0.15} | D ^{+0.30} _{-0.30} |
| 06 | 5.08 | 7.52 | 10.06 | 7.62 |
| 08 | 7.62 | 10.06 | | |
| 14 | 15.42 | 17.68 | | |
| 16 | 17.78 | 20.22 | | |
| 18 | 20.32 | 22.76 | | |
| 20 | 22.86 | 25.30 | | |
| 22 | 25.40 | 27.84 | | |

UNIT: mm

繪圖 DRAWN BY
FUFU

日期 DATE
2008/12/15

核對 CHECKED BY
WENDY

比例 SCALE
1:1

圖號

DRAWING NO.